OUC's All-In-One Photovoltaic Sensor Phase II

Group 6

Sponsored by The Orlando Utilities Commission, OUC



GROUP 6




Timothy Ajao (BSEE)



Marco Herrera (BSEE)



Andrew Hollands (BSCpE)



Maguire Mulligan (BSEE)


Faculty & Sponsor

Mark Steiner – Faculty Advisor

ChungYong Chan – Technical Advisor

Rubin York – OUC Contact





Solar Power is becoming more appealing


- Provides clean, renewable energy
- Reduces reliance on traditional fuels
- Installed and managed on-site

To ensure Solar Panels are working their best, they must be monitored

- Generation is not obvious, therefore issues are not
- Small issues can heavily decrease power generation
- Solar Monitoring solutions exist, but can be expensive or reliant on others.

Rubin York aims to create a simple sensor that can monitor a panel locally

- Traditional monitoring methods depend on third party companies
- The All-In-One Photovoltaic Sensor will be this product
- Able to measure and record generated voltage & current and a panel's temperature
 & irradiance



DESIGN GOALS & REQUIREMENTS


This project is a continuation of a previous Senior Design project, considering us to be Phase II. In Rubin's new vision, the following will be implemented.

The All-In-One PV Sensor (AIO PV Sensor) should be able to

- Withstand as much as 40 Volts, DC at 10 Amps
- Measure a Solar Panel's voltage, current, temperature and irradiance
- Transmit the 'Panel-Level' data wirelessly to a local node for data storage
- Connect via MC4 connections to be inserted in existing Solar Array strings

With these restraints, the AIO PV Sensor will accomplish

- Creating a simple sensor that can be installed on existing arrays
- Allowing OUC to have easy access to Panel-Level data
- Having a locally managed database for data analysis
- Reducing the reliance on third parties to read Panel-Level Data



SPECIFICATIONS

Sponsor Requirements

| Requirement | Priority |
|---|----------|
| Capable of handling & sensing 40 V, 10 A, DC. | High |
| Modular design for Temperature & Irradiance Sensing | High |
| MC4 Insertion or Connections | High |
| Wirelessly communicate with local node for data storage | High |
| About or below \$20 per sensor | Moderate |
| Plastic enclosure capable of withstanding outdoors | Low |
| Year-long lifespan | Low |

Engineering Requirements

| Requirement | Constraint |
|-------------------------------|--|
| Voltage Accuracy | ±5% of actual value |
| Current Accuracy | ±5% of actual value |
| Temperature Accuracy | ±5% of actual value |
| Irradiance Accuracy | ±5% of actual value |
| Data Transmission Interval | <10 seconds between datapoints |
| Wireless protocol | Self-Generated Wi-Fi or Bluetooth |
| PCB Power | Powered by Panel Generation, no external battery |

DESIGN APPROACH AND PROPOSED IMPLEMENTATION




Phase II design approach:

- Analyze Phase I attempt.
- Analyze phase I cost per unit assuming everything worked.
- Fixing or redesign "All-in-One-PV Sensor" design from phase I.
- Lower Research Cost by using Phase I Raspberry Pi 4 for the main data storage node.
- Research cost effective system components for every major sensor circuit.
 - Multifunction Integrated chips reduces board size and complexity.

Phase II design Implementation:


 ESP-32 based sensing node for transmitting sensor data via WIFI and interpreting sensors input signal.






HARDWARE BLOCK DIAGRAM


Data is collected from each sensing component: thermocouple, pyranometer, voltage sensor, and current sensor. Once these devices have collected data, the ESP32 microcontroller will organize the data into a string which will then be sent to the Raspberry Pi microprocessor via a dedicated ESP32 access point and then parsed into a MySQL database.



SENSING AMPLIFIER







| | TLV342A | INA216 |
|----------------|------------------------------|------------------------------|
| Feature | Low-Voltage Rail-to- Rail | High precision current sense |
| Supply voltage | 5.5 V < Vin > 1.5 V | 5.5 V < Vin > 1.8 V |
| No. Op Amp | Two | One |
| Price | \$0.323 | \$0.442 |






Current Shunt:

- One Milliohm shunt resistor
- Power Rating Of 4 W can handle 8.91 A


Voltage drop Across the Shunt is measured, and it is sent to ADC

Very small voltage drop to measure, therefore amplification is needed





VOLTAGE REGULATOR-LMR36015



- 4.2 V 60 V Buck Converter
- Supplies 3.3 V and up to 1.2 A
- o Readily available for purchase





Wire

Price

Mount


To select the best thermocouple, we can implement in our design we most take the following in consideration:

Type

Response

Operation

- Cost-effective with out mitigating performance.
- Fast Response Time.
- Easy to mount on solar cell without extra hardware.
- Highly Linearized for maximum accuracy.
- Weatherproof for outdoor use.



| 2. | Time | Temperature Range | | Option | Insulatio n | |
|----|----------|----------------------|--------------------------|-------------------|----------------|---------|
| J | 0.4 Sec. | 0°C to 1400 °C | Iron-Constantan | N/A | PFA | \$90.36 |
| Т | 0.3 Sec. | 0°C to 600 °C | Copper Constantan | Self- Adhesive | PFA | \$83.99 |
| E | 0.2 Sec. | 0°C to 1600°C | CHROMEGA™- Constantan | N/A | PFA | \$100 |
| K | 0.3 Sec. | 0°C to 3500 °C | CHROMEGA™- ALOMEGA™ | Self- Adhesive | PFA | \$83.98 |

Material

THERMOCOUPLE SIGNAL CONDITIONING SELECTION





| Conditioning System IC | Thermocouple Compatible | Resolution | ADC | Operational Voltage | Detection | Price |
|------------------------|--|-------------|--------|------------------------|---------------------------|---------|
| MAX6675 | Type T and Type K | 0.25°C | 14-bit | 3V-5V | Open Circuit | \$6 |
| MAX31885 | Type K, Type T, Type J, Type S, Type R, Type N, and Type E | 0.0078125°C | 12-bit | 3V- 3.6V | Short and Open Circuit | \$17.50 |




For a sensor such as the All-In-One PV Sensor, a pyranometer is commonly used to measure irradiance.

For this application, the Pyranometer must be able to be removed with no impact to the primary functionality of the PCB. OUC decided that the cost of the pyranometer would not be considered in the final sensor cost.

Despite this, a cheap and self-standing solution was needed to successfully implement a pyranometer to our All-In-One PV Sensor.



















| Pyranometer | SP-110-SS | SP-510-SS | CS320 |
|---------------|----------------|----------------|----------------|
| Technology | Silicon-Cell | Thermopile | Thermopile |
| Output | Analog, ~100mV | Analog, ~400mV | Digital Signal |
| Power Supply | Self-Powered | Self-Powered | 6~24 VDC |
| Response Time | <1ms | 0.5 s | 2 s |
| Average Cost | \$230 | \$330 | \$524 |











| Pyranometer | MAX4194 | MCP3008 | INA126 |
|----------------|------------------------------|-------------------------|------------------------------|
| Technology | Instrumentation Amplifier | Pseudo-Differential ADC | Instrumentation Amplifier |
| Voltage Supply | 2.7 - 7.5 V | 2.7 – 5.5 V | 0 – 36 V |
| Current Supply | 93μΑ | 500μA maximum | 10 mA |
| Output | Voltage, 0-3V | Digital Signal | Voltage, 0-3V |
| Average Cost | \$6 | \$3 | \$4 |

MICROCONTROLLER IMPLEMENTATION







| Microcontroller | ESP32 | Raspberry Pi Zero |
|-----------------|--|---------------------------------------|
| CPU | Xtensa single-core 32-bit LX6 microprocessor, 240Mhz | Broadcom BCM2835 1Ghz, Single-core |
| RAM | 520KB | 512MB |
| Wi-Fi/Bluetooth | Yes | Yes |
| Power | 3.3V or 5V, supplied via GPIO pins or 5V, supplied via micro USB connector | 5V, supplied via micro USB connector |
| Average Cost | \$5 | \$10 |



MICROPROCESSOR IMPLEMENTATION

The microprocessor we chose for our design is the Raspberry Pi 4 Model B+. The Raspberry Pi features everything we need for our design, such as a programmable operating system, Wi-Fi and Ethernet, HDMI/video ports, and USB.

Additionally, with a microSD port for the main storage, the Raspberry Pi can utilize up to 2 TB of storage. For our purposes, we have chosen a 128 GB microSD card that stores our operating system and MySQL database with over 100 GB to spare for years' worth of datapoints.






MICROCONTROLLER PROGRAM FLOW

At the start of the ESP32's C code, each GPIO pin that will be used to transmit data from the collecting sensors to the microprocessor will be initialized.

Next, the ESP32 establishes a Wi-Fi connection to the microprocessor's MySQL database via a PHP script.


Finally, the ESP32 will post collected data to the microprocessor's MySQL database until powered off.





MICROPROCESSOR PROGRAM FLOW

The Raspberry Pi will house multiple programs to support the wirelessly connected AIO PV Sensor. The software bundle installed on the microprocessor can be referred to as a LAMP (Linux, Apache, MySQL, PHP) server. The LAMP server uses each of its components in tandem to be able to wirelessly receive and post collected data to an HTML webpage. It is called a LAMP server because the Linux operating system controls the Apache server and data is queried using MySQL and PHP scripting.







SensorData (ESP32)

+ ssid: string

+ password: string

+ apiKeyValue: string

+ sensorName: string

+ sensorLocation: string

+ themoDO: int

+ themoCS: int

+ thermoCLK: Int

+ conv: float

+ pcf: float

+ adcValue: int

+ voltValue: float

+ volt: int

+ adcValue1: int

+ ampValue: float

+ amp: int

+ sensorLocation: string

+ httpRequestData: string

| ID | |
|-------------|---|
| Sensor | |
| Location | |
| Temperature | 8 |
| Irradiance | |
| Voltage | |
| Current | |
| Timestamp | |

SensorData (MySQL Database)

| ID | Sensor | Location | Temperature (°C) | Irradiance (W/m^2) | Voltage (V) | Current (A) | Timestamp |
|----|--------------|-------------|------------------|--------------------|-------------|-------------|---------------------|
| 1 | AIOPVSensor1 | SolarPanel1 | 32.50 | 62.8 | 35.5 | 6.30 | 2022-04-15 08:00:12 |
| 2 | AIOPVSensor1 | SolarPanel1 | 32.25 | 62.9 | 35.1 | 6.31 | 2022-04-15 08:00:13 |
| 3 | AIOPVSensor1 | SolarPanel1 | 32.00 | 63.1 | 35.4 | 6.24 | 2022-04-15 08:00:14 |
| 4 | AIOPVSensor1 | SolarPanel1 | 31.50 | 63.5 | 35.3 | 6.5 | 2022-04-15 08:00:15 |







There were some difficulties encountered along the way of designing the software running on the Raspberry Pi. Those difficulties include being unable to set a static IP address. We sought to set a static IP address for the Raspberry Pi so our ESP32 could easily access post data to the Raspberry Pi without having to modify the IP address included in the ESP32's code. Additionally, we ran into some issues with modifying the SQL query code to add additional columns for more datapoints.



PCB SCHEMATIC FOR V1.0







TLV342A CURRENT SENSING

Noninverting Differential gain amplifier:

- Amplifies Shunt Voltage
- \circ Rin = 1.15 K Ω
- \circ Rf = 334 K Ω
- \circ Av = 291
- Voltage sent to the ADC

Ohms Law will be used to obtain current value










Voltage leaving solar panel is too high.


Voltage divider:

- o Reduces 39 V to 1.77 V
- \circ R1 = 105 K Ω (*2)
- \circ R2 = 10 K Ω

Unity gain buffer:

- Reduces Power consumption
- o Reduces Noise






CURRENT AND VOLTAGE SENSING PCB IMPLEMENTATION

The TLV342 will have application in both the current and voltage sensing on the PCB.

Gain Resistors would amplify the voltage across the shunt, which would then be sent to the ADC of the ESP 32.

Voltage divider reduces voltage for measuring, then unity gain buffer will send the voltage to the ADC of the ESP32.


ESP32 send Data collected to a node.




TEMPERATURE PCB IMPLEMENTATION




The MAX6675 was the most cost-effective component that we could use in our implementation that does not compromise thermocouple compatibility and resolution.



Even if only has 12-bit digital resolution, compared to the MAX31885. MAX6675 has a 0.25°C resolution that falls within require +/- 10% temperature offset.






The thermocouple utilized in this application is both a Type T and Type K thermocouple self-adhesive.


IRRADIANCE IMPLEMENTATION DIFFICULTY

Initially, the MAX4194 was selected to amplify the pyranometer's signal to send to the ESP32's on-board ADC.

The datasheet was misleading, as the part advertised full functionality under a single supply. Due to the pyranometer's low and differential output, the signal could not properly be amplified without saturation.

Early tests showed that when operating on a single supply, the measured irradiance error grows as exposure to sunlight increases due to low comparative voltages.








IRRADIANCE PCB IMPLEMENTATION


The MCP3008 was selected as the most practical and affordable option to integrate the SP-110-SS Pyranometer into the PCB.

Although it has a 10-bit resolution, it offers a pseudo-differential input reading and a low price point combined with high part availability. The pseudo-differential input allows the differential signal to be easily translated into a digital one.

This choice cut the price of integrating the pyranometer by half and greatly simplified the means of translating the signal to digital.




















For the first porotype we decided to implement an ESP-32 developmental board for our preliminary testing. This was done for various factors when it comes to testing such as:


- Stress test the DC-DC Stepdown Converter with high voltage.
- Ease of multipoint probing.
- Allows ease of ESP-32 replacement incase of failure.








PROBLEMS AND DIFFICULTIES



Current Sensing


 PCB Layout Noise introduction due to part spacing.

o PCB 4 layers adding complexity.












BUDGET

Gross Budget: \$2000




■ Remaining













Ordered PCB 5/20

Components Soldered 6/3 Field Testing 6/13

Receive PCB 6/23 Test PCB 7/1



















Received PCB 5/26

Testing Sensors on PCB 6/6 Redesign and order PCB 6/16 Solder Components 6/28

THANK YOU



Any Questions?

